

SignalIX iMossa SX-08X IP-MPLS ROUTER

- ❖ **SignalIX iMossa Series MPLS-IP Router** can provide stable, reliable, secure high-performance L2/L3 switching services. G-Series MPLS-IP switch products can provide 40G to 800G switching capacity, with various port types, and can provide E1, STM-1, GE, GE(O), 10GE, 100GE interfaces to meet the network deployment requirements from access to aggregation and core layer. **SignalIX iMossaSX-08X IP-MPLS Router** is designed to meet the new challenges and requirements that wide deployment of advanced services needed from networking. The router has the following benefits
- ❖ SignalIX advanced software and hardware architecture, which uses the most high-performance multi-core processor, provides superb concurrent service processing capabilities & unparalleled network performance with 80 Gbps backplane.
- ❖ Support L2/L3 VPN, IPv4/IPv6 static and dynamic routing, sub-50ms protection LSP/PW 1:1, LAG, SNCP, dual-homing, VRRP Support IEEE 1588v2, SyncE and zero-touch provisioning.
- ❖ It supports Branch Intelligent Management System (BiMS) which allows batch software upgrade, automatic configuration issuing, configuration rollback, operation monitoring, and fault alarm. Comprehensive network management methods—Supports command line and SNMP.
- ❖ **KeyFeatures:**
 - FE/GE/10GE Interfaces
 - High Performance & Stability
 - Standard IP-MPLS Technology
 - Power, FAN & OAM Redundancy
 - Powerful & Simple Management
 - Support BFD and Ethernet OAM

- ❖ **Protocols and Standards:**

- **IEEEProtocols:**802.1p,802.1Q,802.1ad,802.3ad,802.3ah,802.1ag,802.3x,802.3z,802.3ab,802.3ac, 802.3ae, 1588v2
- **RFCs** :1112,1850,2236,2370,2439,2457,2474,2475,2544,2547,2554,2597,2598,2740,3101, 3107,3140,3246,4364,4448,4618,4761,4762,4842,6020,6241,7011,7012
- **ITU-TSpecification:**Y.1731,G.8113.1,G.8113.2,Y.1564

Hardware Specifications:

FEATURES	SPECIFICATIONS
Product Name & Model	SignalIX iMossa SX-08X IP-MPLS Router
Rack Type	1RU,19" Rack mount
Full duplex switching capacity	80 Gbps
Console Management Port	1
Max power consumption	75 W
Power module redundancy	Dual AC (220 V +/- 20%) Redundant Module & Hot Swappable
Cooling FAN	Hot Swappable and Redundant Fans
Interfaces Support	<ul style="list-style-type: none"> • 10G Port - 4 Ports • 1G/10G Port - 4 Ports • 1G Port - 4 Ports
Environment standards	QM 333 certified

Detail Features:

MPLS	<ul style="list-style-type: none"> • MPLS, SRMPLS, LDP, MPLS Class of service
L3Protocols	<ul style="list-style-type: none"> • OSPF, OSPFv2 and OSPFv3, eBGP, IBGP, ISIS, ECMP, PIM SM/SSM, • Pv4/IPv6 static and dynamic routing
Full Carrier Ethernet Functions	<ul style="list-style-type: none"> • L2/L3VPN, EPL, EVPL, VLL, E-LAN and VPLS, E-LAN, E-LINE, E-TREE. • Ethernet OAM, QOS, BFD, L2MAC address Learning, CE Simulation • VLAN per IEEE 802.1Q and IEEE 802.1ad, Jumbo Frames • Port Mirroring, IGMPv2 and v3, IEEE 1588v2, NTP and SyncE. • 2048KHz Timing interface for external Synchronization. • DHCP, MPLS TE or RSVP or SRTE, TI-LFA, R-LFA, STP, RSTP, MSTP. • ERPS/ITU-TG.8032v2, Open ERPS, LLDP, LLC, Flow Control. • Link Aggregation. LACP, Egress Buffering, PWE3
Security	<ul style="list-style-type: none"> • RADIUS, GTSM, DoS attack prevention • MAC address limitation and aging, MAC address spoofing prevention • Traffic Filtering, TACACS+, CAC
Equipment Redundancy & Protection	<ul style="list-style-type: none"> • LSP 1:1 protection, PW 1:1 protection, LAG, SNCP, ERPS • Dual-homing protection, VRRP
Ease of Deployment & Simple Management	<ul style="list-style-type: none"> • Zero touch provisioning, SDN integration based on Net conf/YANG • PCEP, segment routing, SNMP v2/V3